


Intelligent 8 **Smart PoE Switch**

Specification



Feature

- Using CAT.5 network cable support power for the Access Point and IP camera
- Networking standard: IEEE802.3af/t
- Long distance transmission and power supply, maximum transmission distance is 130m
- Upload port support Auto MDI / MDIX
- Forwarding Mode: Store-and-forward
- Intelligent power distribution and secure power supply system
- Power circuit protection function can protect environment
- Zero configuration feature power supply is automatically supplied to the adaptive equipment
- 6KV Professional thunder design, high reliability, high stability
- Nature cooling, small, compact, mute, all the designs are convenient for you to put
- Reduce the no-load loss
- 10/100Mbps 1-8port up link or PoE port can be converted to each other



Model HG-SW8 8P8

Network Interface PoE (1~8) up-Link (1-8), Automatic flip (Auto MDI / MDIX)

(10/100M 8 uplink or 8 PoE port can be converted to each other)

Network Standard IEEE802.3af/t Long Distance Transmission Max 130M.

Network performance Store-and-forward

Transmission Rate 100Mbps Full Duplex; 10 or 100Mbps Half Duplex

10BASE-T or 100BASE-TX RJ45 port of ethernet

Perfomance&Specification Bandwidth: 2 Gbps

Network Latency (10 to 100Mbps):20µs

(use the 64 byte packge size)

MAC address table: 1K

The Frame Filter & Transmission Rate 14800pps the most for 10M port

148800pps the most for 100M port"

IEEE 802.3i 10BASE-T **Networking Standard**

IFFF 802 3u 100RASE-TX

IEEE 802.3x Flow Control

IEEE 802.3af/at Power over Ethernet

PoE Core of Power Cable Default: 1/2(+), 3/6(-); (Can Be Selected 4/5(+), 7/8(-))

Power Support Power input: AC 110~220V/150W

Power output: PoE1~4Port1/2(+52V),3/6(GND)

Size (LxWxH) 187mmx139mmx43mm

Operating Temperature -10c~+40c (-14~104F)

Storage Temperature -40c~+70c (-104~158F)

Operating Humidity 10%~90% non-condensing

5%~90% non-condensing Storage Humidity

Electromagnetic Compatibility CE mark

FCC Part 15, Class B

C-Tick

Lightning Protection Support

Intelligent power distribution

Secure power supply system

Port no-load Saving Power

Power circuit protection

Overtemperature protection

Short circuit protection

Package Content

VCCI Class B EN 55022 (CISPR 22)

Support

Support

Support

Support

Support

Support

AC Power Cable, Installation Manual Warranthy Card