


Intelligent 14+2+1 Smart PoE Switch

Specification

14-2-1 Smart FoE Switch

Feature

- Using CAT.5 network cable support power for the Access Point and IP camera
- Networking standard: IEEE802.3af/t
- Long distance transmission and power supply, maximum transmission distance is 130m
- Upload port support Auto MDI / MDIX
- Forwarding Mode: Store-and-forward
- Intelligent power distribution and secure power supply system
- Power circuit protection function can protect environment
- Zero configuration feature power supply is automatically supplied to the adaptive equipment
- 6KV Professional thunder design, high reliability, high stability
- Nature cooling, small, compact, mute, all the designs are convenient for you to put
- Reduce the no-load loss
- 10/100/1000Mbps 15-16port up link or PoE port can be converted to each other



Model HG-SW17 3P16

up-Link(15-16)/LAN

Network Interface PoE(1~16)

Network Standard IEEE802.3af, IEEE802.3at

Long Distance Transmission Max.130M.

Network performance Store-and-forward

Transmission Rate 1000Mbps Full Duplex; 10 or 1000Mbps Half Duplex

10BASE-T or 1000BASE-TX RJ45 port of Ethernet

Perfomance&Specification Bandwidth: 8.8 Gbps (no barriers)

Network Latency(10 to 1000Mbps): \leq 20 μ s

(use the 64 byte packge size)

MAC address table: 8K

The Frame Filter & Transmission Rate

14800pps the most for 10M port

148800pps the most for 100M port

Networking Standard IEEE 802.3i 10BASE-T

IEEE 802.3u 100BASE-TX

IEEE 802.3x Flow Control

IEEE 802.3af/at Power over Ethernet

PoE Core of Power Cable Default: 1/2(+), 3/6(-); (Can Be Selected 4/5(+), 7/8(-))

PWR light alwys on

Power Support Power input: AC 180~240V 250W

Power output: PoE port 1-16, 1/2 (+52V),

3/6(GND), DC 5525 5V1A

Size (LxWxH) 430mmx180mmx45mm

Operating Temperature -10c~+40c (-14~104F)

Storage Temperature -40c~+70c (-104~158F)

Operating Humidity 10%~90% non-condensing

Storage Humidity 5%~90% non-condensing

Electromagnetic Compatibility | CE mark

FCC Part 15, Class B

VCCI Class B EN 55022 (CISPR 22)

C-Tick

Support

Lightning Protection 6KV

Port no-load Saving Power

Package Content

LEDs Light

AC Power Cable, Installation Manual Warranthy Card