



PRO SERIES

ProCapture-T

Fingerprint Access Control Reader

ProCapture-T is a next-generation access control reader utilizing advanced SilkID fingerprint sensor technology.



Biometric Performance:

Reliable, durable and highly accurate SilkID fingerprint sensor with latest fingerprint matching algorithm which provides less than 1.5 second user recognition.



Capacity:

Stores up to 6,000 fingerprint templates and 10,000 cards. Data can be backed up to a USB flash drive and transferred to another ProCapture-T in the absence of network connectivity.



Easy Operation and Management:

Works without a computer. Complete setup and programming can be done via the ProCapture-T keypad and embedded firmware. Audio-Visual Indication for acceptance and rejection of valid/invalid fingerprints, cards and passwords.



Options:

Internal Proximity Card or Mifare Card reader allows dual factor authentication for access control.



Communication:

Weigand output for connecting to an access control panel and Ethernet port for fast and reliable network communication.



Full Access Control Built In:

Relay Outputs for electric lock and alarm. Inputs for door status sensor and request to exit hardware. Supports multiple time zones and personnel groups for programming valid entry zones.



For Software Developers:


Free SDK and development tools are available for developers/partners who wish to integrate Pro-Capture-T with any application which requires verifying people. Custom development is also available for OEM partners upon request.




Built-in Camera:

Stores up to 7,000 event snapshots and Stores up to 3,000 user photos.

Configuration



Dimensions



Specifications

Capacity

Fingerprints: 6,000
Cards: 10,000

Access Control Interface

Lock Relay Output
Alarm Output/Auxiliary Input
Exit Button/Door Sensor
Doorbell Output

Communication

TCP/IP, RS485 (for slave reader)
USB Host
Wiegand Input/Output

Hardware

SilkID Fingerprint Sensor
2.4 Inch TFT-LCD Touch Screen
125 kHz ZKAccess Card Reader
Tamper Switch Alarm

Standard Functions

Access Levels/Groups/Holidays
DST/Bell Schedule
Duress Mode (Password)
Anti-Passback
Record Query
Custom Wallpaper & Screen Saver

Software Compatibility

ZKBioSecurity

Additional Info

Working Temperature:
14° F to 122° F (-10° C to 50° C)
Dimensions: 7.7 x 3.5 x 1.4 inches
(195.5 x 87 x 35 mm)
Package Includes: 12V 3A Power Supply

Power

Operating Voltage 12V DC
Current Draw < 500mA

Part Numbers

ProCapture-T

includes ZKAccess card reader

ProCapture-HID

includes HID 125 kHz card reader

ProCapture-Mifare

includes Mifare card reader

ProCapture-iClass

includes HID iClass card reader


What's in the Box



ProCapture-T




Installation Template



Back Plate




Measuring Tape



Network Cable



Screws



AC Power Adapter



Screwdriver



Cables



Diode



ZKAccess

6 Kingsbridge Road, Unit 8, Fairfield, NJ 07004
Phone: (862) 505-2101 • Fax: (862) 204-5906 • sales@zkaccess.com • www.zkaccess.com

© Copyright 2016, ZKTeco Inc. ZKTeco Logo and ZKAccess Logo are registered trademarks of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

